











NOTES:

UNLESS OTHERWISE SPECIFIED:

1. ALL RESISTORS ARE EXPRESSED IN OHMS AND ARE 1/4V, 5%.

2. ALL CAPACITORS ARE EXPRESSED IN HICROFARADS.

3. ALL SZL AND NPD CERAMIC DISC CAPACITORS ARE +/-5%.

4. ALL YSE CERAMIC DISC CAPACITORS ARE +/-28%.

5. ALL ZSU CERAMIC DISC CAPACITORS ARE +/-28%.

6. ALL RADIAL ELECTROLYTIC CAPACITORS ARE +/-28%.

7. ALL OTIODES ARE INAI48.

8. ALL SWITCHES ARE SHOWN IN THE "OUT" POSITION.

9. DENDIES ARE SHOWN IN THE "OUT" POSITION.

18. FIRM DENDIES WOLTAGES ARE TIED TOGETHER AND

RETURN TO CENTRAL GROUND SEPARATELY.

11. EXT CV IN IS SCALED AT -58m/JdB.

22. DENDIES ONLESS ARE INDICATED AMP/HIXER JUMPER CONNECTOR.

SHOWN IN THE "OISTRIBUTION AMP" 
POSITION.

13. DENDTES BALANCED/NDN-BALANCED JUMPER CONNECTOR. SHOWN IN THE "BALANCEO" POSITION.